

Supplier:

Hummel Croton Inc. 10 Harmich Road

(908)-754-1800

Chemical Formula: Variable

Chemical Name: Calcium Resinate Synonym: Calcium Resinate CAS Number: 9007-13-0

South Plainfield, NJ 07080

Hummel Croton Inc. 10 Harmich Road South Plainfield, NJ 07080

Tel:908-754-1800 / Fax 908-754-1815

**MSDS** 



**Calcium Resinate** 

In case of Emergengy Call Chemtrec ® (U.S.) (800)-424-9300 (International) (703)-527-3887

## **Section I. Chemical Product and Company Identification**

HMIS Rating	
Health	1
Flammability	3
Reactivity	1
Personal Protection	Е

# Section II. Composition and Information on Ingredients

Material	CAS#	%	OSHA	ACGIH
Calcium Resinate	9007-13-0	100%	Not Established	Not Established

Since no Exposure limits have been established for Calcium Rseinate by OSHA & ACGIH, we recommend that our product should be treated as a nuisance dust 15 mg/m<sup>3</sup>.

## **Section III Hazards Identification:**

*Accute Health Effects:* Irritating to the skin and eyes on contact. Inhalation will cause irritation to the lungs and mucus membrane. Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are characteristics of skin inflammation. Follow safe industrial hygiene practices and always wear protective equipment when handling this compound.

*Chronic Health Effects:* This product has no known chronic effects. Repeated or prolong exposure to this compound is not known to aggravate medical conditions.

Accute Health Effects: This product is not listed by NTP, IARC or regulated as a Carcinogen by OSHA.

### **Section IV. First Aid Measures**

*First Aid For Eye:* In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. *First Aid For Skin:* In case of contact, flush skin with water. Wash clothing before reuse. Call a physician if irritation occurs. *First Aid For Inhalation:* If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

First Aid For Ingestion: If swallowed, call a physician immediately.

## Section V. Fire and Explosion Data

Flammability: Non-Flamable
Flash Points: Not Applicable
Auto-Ignition: Not Applicable
Flammable Limits: Not Applicable
Extinguishing Media: Water Fog or Mist, Carbon Dioxide, Dry Powder, and Foam
Fire Fighting Procedure: Avoid using water other than a fog or a mist. Fire fighters need self contained respiratory equipment for fires in enclosed areas.
Fire/Explosion Hazards: Resin dust is an explosive hazard in air. May form FLAMMABLE dust-air mixture. Static charges generated

*Fire/Explosion Hazards:* Resin dust is an explosive hazard in air. May form FLAMMABLE dust-air mixture. Static charges generated by emptying packages in or near FLAMMABLE vapors may cause a flash fire.

#### **Section VI. Accidental Release Measures**

Spill Or Leak Procedures: Utilize recommended protective clothing and equipment. Clean spills in a manner that does not disperse dust into the air. Spill area can be washed with water. Collect wash water for approved disposal. Keep from entering water or ground water

### Section VII. Handling and Storage

Storage Temperatures: Store at ambient temperature

Shelf Life: Unlimited in tightly closed container.

Special Sensitivity: None

Handling/Storage Precautions: Avoid breathing dust. Avoid getting in eyes or on skin. Wash thoroughly after handling. Store in a dry place away from direct sunlight, heat and incompatible materials (see Section X). Reseal containers immediately after use. Store away from food and beverages.

### Section VIII. Exposure Controls/Personal Protection

Eye Protection: Safety glasses or goggles.

*Skin Protection:* PVC gloves with impervious boots, apron or coveralls. Employees should wash their hands and face before eating, drinking or using tobacco products.

*Respirator:* Work ambient concentrations should be monitored and if the recommended exposure limit is exceeded, a NIOSH/MSHA approved dust respirator must be worn.

Ventilation: Use local ventilation if dusting is a problem, to maintain air levels below the recommended exposure limit.

Additional Protective Measures: Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous chemicals.

### Section IX. Physical and Chemical Properties

Physical Form: Fine Powder Color: Tan to White Odor: Mild Pine Odor Molecular Weight: Variable Boiling Point: Above 260°C Melting/Freezing Point: Above 175°C Solubility In Water: Slightly Specific Gravity: Not Established

## **Section X. Stability And Reactivity**

 Stability:
 Stability:

 Stability:
 Stability:

 Hazardous Polymerization:
 Will Not occur

 Incompatibilities:
 Avoid mixing with strong oxidants.

 Instable Conditions:
 Excessive temperatures (see Incompatibilities).

 Decomposition Temperature:
 Not Established

 Decomposition products:
 Carbon Monoxide, Carbon Dioxide, Oxides of Calcium

## Section XI. Toxicological Infomation

RTECS Number: EW 397-0000

Routes of Exposure: Eye contact. Ingestion. Inhalation. Skin contact.

Toxicity Data: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Chronic Toxic Effects: This product has no known chronic effects. Repeated or prolong exposure to this compound is not known to

aggravate medical conditions.

*Acute Toxic Effects:* Irritating to the skin and eyes on contact. Inhalation will cause irritation to the lungs and mucus membrane. Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are characteristics of skin inflammation. Follow safe industrial hygiene practices and always wear protective equipment when handling this compound.

#### Section XII. Ecological Information

Ecotoxicity: Not available at this time.

#### Section XIII. Disposal Considerations

Waste Disposal Method: Waste disposal should be in accordance with existing federal, state and local environmental regulations.

#### Section XIV. Transportation Information

Proper Shipping Name: Calcium Resinate UN Number: 1313 Class: 4.1 P.G.: III Label Code: 4.1

#### Section XV. Regulatory Information

**OSHA Status:** This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Chemical Inventory: This compound is on the EPA Toxic Substance Control Act (TSCA) inventory List

*California Proposition 65:* To the best of our knowledge, this product contains no levels of listed substances, which the state of California has found to cause cancer, birth defects or other reproductive effects.

SARA 313 Title III:

Section 302 ExtremelyHazardous Substances: None Section 311/312 Hazardous Categories: None Section 313 Toxic Chemicals: None

#### **Section XVI. Other Information**

Prepared By: Mark Dugan Date: January 05, 2009 Reason For Issue: Updated Format

No warranty, expressed or implied, or merchantability, fitness for a particular purpose or otherwise is made, except that the products herein discussed comply with the chemical description on the labels. Buyer assumes risks of the use, storage and handling. Hummel shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge, true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions. This information is not to be taken as a license to operate under, or a recommendation to infringe any patent(s). The observance of all regulations and patents is the responsibility of the user. No agent, representative or employee of this company is authorized to vary any terms of this notice.